

*JFW*  
ERSO-87-076C

April 30, 2004



To: Commissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

Fr: George O. Saile, Reg. No. 19,572  
28 Davis Avenue  
Poughkeepsie, N.Y. 12603

Subject: | Serial No. 10/812,735 03/30/04 |  
| Lai-Juh Chen |  
| CHEMICAL MECHANICAL POLISH PROCESS |  
| CONTROL METHOD USING THERMAL IMAGING |  
OF POLISHING PAD
-----

#### INFORMATION DISCLOSURE STATEMENT

Enclosed is Form PTO-1449, Information Disclosure Citation  
In An Application.

The following Patents and/or Publications are submitted to  
comply with the duty of disclosure under CFR 1.97-1.99 and  
37 CFR 1.56.

#### CERTIFICATE OF MAILING

I hereby certify that this correspondence is being  
deposited with the United States Postal Service as first class  
mail in an envelope addressed to: Commissioner for Patents,  
P.O. Box 1450, Alexandria, VA 22313-1450, on May 4, 2004.

Stephen B. Ackerman, Reg.# 37761

Signature/Date

*Stephan B. Ackerman* 5/4/04

U.S. Patent 5,647,952 to Chen, "Chemical/Mechanical Polish (CMP) Endpoint Method," describes a method for endpoint detection in CMP in which infrared detection is used to measure the temperature of a selected polishing pad location which is abrading the surface of the semiconductor substrate.

U.S. Patent 5,234,868 to Cote, "Method for Determining Planarization Endpoint during Chemical-Mechanical Polishing," describes a monitor structure surrounded by a moat.

U.S. Patent 5,240,552 to Yu et al., "Chemical Mechanical Planarization (CMP) of a Semiconductor Wafer using Acoustical Waves for In-Situ End Point Detection," directs acoustical waves at the wafer during CMP and through analysis of the reflected wave form controls the planarization process.


U.S. Patent 5,308,438 to Cote et al., "Endpoint Detection Apparatus and Method for Chemical/Mechanical Polishing," describes an endpoint detection method in which the power required to maintain a set rotational speed in a motor rotating the substrate is monitored.

U.S. Patent 5,337,015 to Lustig et al., "In-Situ Endpoint Detection Method and Apparatus for Chemical-Mechanical Polishing using Low Amplitude Input Voltage," utilizes electrodes built into the polishing pad, and a high frequency, low voltage signal, and detection means as a method for measuring the thickness of a dielectric layer being polished.

U.S. Patent 5,413,941 to Koos et al., "Optical End Point Detection Methods in Semiconductor Planarizing Polishing Processes," describes a method for endpoint detection for polishing by impinging laser light onto the substrate being polished and measuring the reflected light.

U.S. Patent 5,196,353 to Sandhu et al., "Method for Controlling a Semiconductor (CMP) Process by Measuring a Surface Temperature and Developing a Thermal Image of the Wafer," describes the use of infrared radiation detection to measure the surface temperature of a semiconductor wafer during a polishing process.

Sincerely,



Stephen B. Ackerman,  
Reg. No. 37761



**INFORMATION DISCLOSURE CITATION  
MAY 06 2004 IN A N APPLICATION.  
(Use space if necessary)**

MAY 06 20

(Use ~~sug~~al shouls il necessary)

Doctor Number (Optional)

ERSO-87-076C

Assignment Number

10/8/2, 735

Arctans

Lai-Tuh Chen

FHog Dm

03/30/04

Draw An Unit

U. S. PATENT DOCUMENTS

## FOREIGN PATENT DOCUMENTS

**OTHER DOCUMENTS** (including Author, Title, Date, Portion or Pages, Etc.)

Съчинение

DATE CONSIDERED

**EXAMINER:** Initial if citation considered, whether or not citation is in conformance with MPEP § 609; Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to the applicant.